



NEUTRAL POWDER

Neutralizing concentrated powder with inhibitor for steel, stainless steel, cooper, cast-iron, aluminum, brass, tin, light alloys, galvanized surfaces.

1 Kg - COD. 300502002

10 Kg - COD. 300502003

CHEMICAL AND PHYSICAL FEATURES

FORMAT	1 kg/10 kg
PHYSICAL ASPECT	Powder
ODOUR/FRAGRANCE	Odorless
COLOUR	white
pH	11
DOSAGE	3-5%

PACKAGING FEATURES

	1 kg	10 kg
N. OF PIECES PER BOX	6	1
N. OF PCS PER EPAL PALLET	1920	60
BOX DIMENSIONS	H: 16 L:23,5 P: 34	H: 27,5 x Ø26
EPAL PALLET DIMENSIONS	80x120x185	80x120x145
PRODUCT WEIGHT	1,082	10,4
BOX WEIGHT	1,275	10,4
EPAL WEIGHT	698	644
CUSTOMS CODE*	2815.12.00	2815.12.00
BARCODE EAN 13	8054633849453	8054633849446

*Data updated in May 2016

ADVANTAGES

- Neutralizing alkaline solution
- Fast and safe neutralization
- Acid debris elimination
- Non-caustic

BENEFICI

- Neutralizing alkaline solution
- Fast and safe neutralization
- Elimination of acid debris
- Non-caustic

MAIN FEATURES

Neutral Powder is a product in powder, studied for the rapid and safe neutralization of acid-based liquids, employed for the descaling process. After the cleaning with acid-based liquids of systems or heat exchangers of boilers, the solution contained inside the tank of the pump, remains highly acid and it would be necessary an alkaline treatment in order to exhausts the solution used with acid-based products.

What is here above expressed, is more valid for all pipes of treated systems, heat exchanger pipes and the pump used for the descaling process. Neutral Powder is indicated to balance the pH from 6 to 8,5 and, at the same time to neutralize systems, pipes, heat exchangers, and the same pump used to treat, avoiding its corrosion.

APPLICATION AND USE

As highest indication, as it cannot be prevue how much active acid is still present inside the solution, at the end of the treatment, it is suggested for a backwash systems, a solution diluted into water in a percentage of 2-3%.

Operations:

1. Pour the acid solution used, from the pump into a suitable plastic container as containment.
2. Insert inside the tank of the pump, a sufficient quantity of water to do a backwash cleaning of the system, add to the water a quantity of Neutral Powder in a percentage of 2-3% and let it circulate inside the system or inside the device for at least 5 minutes.
3. After having done the backwash cleaning, pour the alkaline solution used inside the bucket that contains the acid solution, previously made inside the container for the neutralization.

SIMILAR PRODUCTS

1. NEUTRAL LIQUID

10 kg - COD. 300502001



1.

TO BE USED WITH

1. Hyperflush 36

COD. 301301001

2. Transformer Combi HF 75

COD. 301301005

3. Transformer Combi HF 110

COD. 301301006

4. Boss Pulce FI

COD. 300601001

5. Boss 5 FI

COD. 300601002

6. Boss 18 - 18 FI

FI - COD. 301301003

COD. 300601004

7. Boss 22 - 22 FI

FI - COD. 300601005

COD. 300601006

8. Boss 36 FI

FI - COD. 300601007

COD. 300601008

9. Boss 100 FI

FI - COD. 300601009

10. Boss 200 FI

FI - COD. 300601010



1.



2.



3.



4.



5.



6.



7.



8.



9.



10.

OFFER DESCRIPTION

Alkaline solution studied for the rapid and safe neutralization of acid-based liquids employed for the descaling process.

COMPLIANCE

NEUTRAL POWDER is a product designed for the treatment of water primary circuit of a heating system. Water treatment of domestic heating systems is specified inside Regulation UNI-CTI 8065/89, decree 26/2015 and Regulations UNI-CTI 8364/84 and UNI-CTI 9317/89. These Regulations respond to European directive 2010/31/UE, concerning the energetic performance inside buildings.

STORAGE

Store the original sealed containers in a cool well-ventilated place, away from heat sources. Keep the container tightly closed if not used. For further information consult the related safety data sheet.

ORIGIN OF THE PRODUCT

 Made in Italy

DS. 394.00
Date of issue: 23/05/2017
Date of revision: 13/11/2017

Boiler Performance by Manta Ecologica S.r.l.
Viale Archimede, 45 - 37059 - Zevio (VR)

www.boilerperformance.com

