



BP COLD F

Anticorrosive, protective for cooling and humidification

10 L - COD. 301201003

20 L - COD. 301201004

CHEMICAL AND PHYSICAL FEATURES

| | |
|--------------------------------------|------------------------|
| PH | 6,79 |
| FORMAT | 10 litres / 20 litres |
| PHYSICAL ASPECT | Liquid |
| DENSITY (KG/DM ³ AT 20°C) | 1,02 g/cm ³ |
| COLOUR | straw-yellow |
| ODOUR/FRAGRANCE | light |
| SOLUBILITY IN WATER | completely miscible |
| DOSAGE | 1% |

PACKAGING FEATURES

| | | |
|------------------------|-------------------|-------------------|
| | 10 L | 20 L |
| N. OF PCS PER BOX | 1 pc | 1 pc |
| PCS PER EPAL PALLET | 60 barrels | 36 barrels |
| BOX DIMENSIONS | H: 33 L: 19 P: 22 | H: 39 L: 24 P: 28 |
| EPAL PALLET DIMENSIONS | 80x120x108 | 80X120X130 cm |
| PRODUCT WEIGHT | 10,45 kg | 20,900 kg |
| BOX WEIGHT | 10,450 kg | 20,900 kg |
| EPAL WEIGHT | 647 kg | 772,4 kg |
| CUSTOMS CODE | 6806.90.00 | 6806.90.00 |
| BARCODE EAN 13 | 8054633849132 | 8054633849071 |

*Data updated in May 2016

ADVANTAGES

- Elimination of microbiological growth
- Increase of system performances
- Prevention of the system obstruction
- Corrosions reduction

BENEFITS

- Low environmental impact
- Reduction of energy consumption visible on your bill
- Extension of the system duration
- Reduction of maintenance costs

MAIN FEATURES

Added to water at the first refill, or when the system is cleaned and drained, prevents corrosion and scales formation. Suitable for being used with all systems, included the ones, containing aluminum components, BP COLD F inhibitor, extends the system duration and guarantees the highest efficiency with the minimum fuel consumption. BP COLD F is a multifunctional treatment for corrossions and scales control in all type of cooling systems, included the ones with aluminum components. BP COLD F may be used with any type of water, both hard and softened. This product assures a protection and has not to be replaced. Its formulation has a low environmental impact.

APPLICATION AND USE

APPLICATION AND USE:

1. Add BP COLD F product directly inside the full system in a concentration of 1% compared to the water volume of the system.
2. Starts the system at a normal operating temperature. Depending on the debris quantity present inside the system, necessary operation time will change. BP COLD F is a not acid product for the prevention of corrosion and scales phenomena inside cooling systems.

SIMILAR PRODUCTS:

1. BP COLD R

10 l - COD. 301201001
20 l - COD. 301201002

2. BP COLD A

10 l - COD. 301201005
20 l - COD. 301201006

3. AIR CLEAN LIQUID

10 l - COD. 301202001
20 l - COD. 301202002

4. AIR CLEAN SPRAY

COD. 301202003

5. PHARMA G DISINFETTANTE

COD. 301202005

6. SPRAY MEDICAL

COD. 301202004



TO BE USED WITH

1. Boiler Mag COD. 300901001



2. MiniMag 3/4" COD. 300901009



3. MiniMag ottone 3/4" COD. 300901010



OFFER DESCRIPTION

Anticorrosive, anti-scaling, inhibitor liquid for cooling systems. To be used after cleaning and restoring operations, or inside new systems. Dose with a concentration of 1% compared to the water volume of the system.

COMPLIANCE

BP COLD F is a product designed for the treatment of water primary circuit of a heating system. Water treatment of domestic heating systems is specified inside Regulation UNI-CTI 8065/89, decree 26/2015 and Regulations UNI-CTI 8364/84 and UNI-CTI 9317/89. These Regulations respond to European directive 2010/31/UE, concerning the energetic performance inside buildings.

STORAGE

Store the original sealed containers in a cool well-ventilated place, away from heat sources. Keep the container tightly closed if not used. For further information consult the related safety data sheet.

ORIGIN OF THE PRODUCT

 Made in Italy

TDS. 368.00
Date of issue: 07/10/2016
Date of revision: 11/12/2017

